

## ダイワ 糸巻き量から見た番手の分布 (LT機種/SF機種)

| 糸巻き量 PE<br>[ナイロン(lb)]                                   | 番手                                | スプール径    | ボディ     | ドラッグ         | 22イグジスト | 23エアリティ | 24エアリティST | ルビアエアリティ | 24ルビアス | 20ルビアス | カルディア | 24セルテート | 19セルテート | 23レグザ | 19レグザ | フリームス | 23レガリス | 18レガリス | レプロス | 23月下美人 | 24月下美人X |   |
|---|-----------------------------------|----------|---------|--------------|---------|---------|-----------|----------|--------|--------|-------|---------|---------|-------|-------|-------|--------|--------|------|--------|---------|---|
| 0.2-210, <b>0.3-200</b> , 0.4-130<br>[2.5lb-100]        | FC LT1000S                        | 40mm     | #1000   | 単板<br>ドラッグ   |         |         |           |          |        |        |       |         |         |       |       |       |        |        |      |        |         |   |
|   | <b>SF1000S</b>                    |          | SF#1000 |              | ○40     | ○40     |           |          |        |        |       |         |         |       |       |       |        |        |      |        |         |   |
|   | LT1000S                           | #1000    |         |              |         |         |           |          |        |        |       |         |         |       |       |       |        |        | ○    | ○      | ○       | ○ |
|   | <b>SF2000SS</b>                   | 42mm     | SF#1000 |              | ○42     | ○42     |           |          |        |        |       |         |         |       |       |       |        |        |      |        |         |   |
| 0.4-200, 0.5-170, 0.6-150<br>[3lb-150]                  | FC LT2000S                        | 42mm     | #1000   |              |         |         |           |          |        |        |       |         | ○       |       |       |       |        |        |      |        |         |   |
|   | <b>LT2000S</b>                    |          | SF#1000 |              | ○42     | ○42     | ○42       | ○42      |        |        |       |         |         |       |       |       |        |        |      |        |         |   |
|   | <b>SF2500SS</b>                   | 45mm     | SF#1000 |              | ○45     | ○45     |           |          |        |        |       |         |         |       |       |       |        |        |      |        |         |   |
| 0.6-200, 0.8-190, 1.0-140<br>[4lb-150]                  | FC LT2500S                        | 45mm     | #1000   |              |         |         |           |          |        |        |       |         | ○       |       |       |       |        |        |      |        |         |   |
|   | <b>LT2500S</b>                    |          | SF#1000 |              | ○45     | ○45     | ○45       | ○45      |        |        |       |         |         |       |       |       |        |        |      |        |         |   |
|   | LT2500S                           | #2500    |         |              |         |         |           |          |        |        |       |         |         | ○45   | ○     | ○     |        | ○      | ○    | ○      |         |   |
| 0.6-290, <b>0.8-200</b> , 1.0-190<br>[6lb-150]          | LT2500                            | 45mm     | #2500   |              |         |         |           |          |        |        |       |         | ○       | ○     | ○     |       |        |        |      |        |         |   |
|   | <b>PC LT2500</b>                  |          | SF#2500 |              | ○45     | ○45     |           | ○45      |        |        |       |         |         |       |       |       |        |        |      |        |         |   |
|   | LT3000S-C                         | 48mm     | #2500   |              |         |         |           |          |        |        |       |         | ○48     | ○     | ○     |       |        |        |      | ○      |         |   |
| 1-200, 1.2-190, 1.5-170<br>[8lb-150]                    | LT3000-C                          | 48mm     | #2500   |              |         |         |           |          |        |        |       |         | ○48     |       |       |       | ○      | ○      | ○    | ○      |         |   |
|   | <b>LT3000</b>                     |          | SF#2500 | ○48          | ○48     |         | ○48       |          |        |        |       |         |         |       |       |       |        |        |      |        |         |   |
|   | LT3000                            | #3000    |         |              |         |         |           |          |        |        |       | ○       | ○       | ○     |       |       |        |        |      |        |         |   |
|   | <b>PC LT3000</b>                  | SF#3000  | ○48     | ○48          |         | ○48     |           |          |        |        |       |         |         |       |       |       |        |        |      |        |         |   |
| 1.2-310, <b>1.5-200</b> , 2.0-170<br>1.2-250 [12lb-150] | LT4000-C                          | 51mm     | #3000   |              |         |         |           |          |        |        |       |         | ○51     | ○     |       |       | ○      | ○      | ○    |        |         |   |
|   | <b>LT4000</b>                     |          | SF#3000 | ○51          | ○51     |         | ○51       |          |        |        |       |         |         |       |       |       |        |        |      |        |         |   |
| 1.0-360, 1.2-300, 1.5-230                               | LT2500D                           | 45mm     | #2500   | LT2500       |         |         |           |          |        |        |       |         |         |       |       |       | ○      | ○      | ○    | ○      |         |   |
| 1.2-430, 1.5-300, 2.0-230<br>1.2-375 [15lb-150]         | LT3000D                           | 48mm     | #3000   | S-DHは<br>単板) |         |         |           |          |        |        |       |         |         |       |       |       |        | ○      | ○    | ○      |         |   |
|   | LT4000D                           |          | 51mm    |              |         |         |           |          |        |        |       |         |         |       |       |       |        |        | ○    |        |         |   |
|   | 1.5-430, <b>2.0-300</b> , 2.5-260 | LT5000-C | 54mm    |              |         |         |           |          |        |        |       |         |         |       |       |       |        | ○      | ○    | ○      |         |   |
| 2.0-350, <b>2.5-300</b> , 3.0-210<br>[20lb-170]         | LT5000D-C                         | 54mm     | #3000   |              |         |         |           |          |        |        |       |         |         |       |       |       |        |        | ○    | ○      |         |   |
|   | LT5000D                           |          | #5000   |              |         |         |           |          |        |        |       |         | ○       | ○54   |       |       |        |        |      |        |         |   |
| 2.5-420, 3.0-300, 4.0-220<br>2.5-360                    | LT6000D                           | 57mm     | #5000   |              |         |         |           |          |        |        |       |         |         |       |       |       |        |        | ○    |        |         |   |

※ 赤字太字は22イグジスト/23エアリティ/23エアリティST/24ルビアスの表記

※ 赤字は糸巻き量の代表値

ベースベース：レプロス-カルディア